

SUNRISE SYSTEM LIGHTING: DOWNLIGHTS

Model (B Series)	Dimension	Opening	Power	Housing Material	Input Voltage		Colour (Kelvin)	Lumen
SR-DD-90003	2.5": Φ90mm*H54mm	Φ78mm	3W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-90004	2.5": Φ90mm*H54mm	Φ78mm	4W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-10003	3": Φ100mm*H50mm	Φ85mm	3W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-10005	3": Φ100mm*H50mm	Φ85mm	5W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-13005	4": Φ130mm*H66mm	Φ118mm	5W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-13007	4": Φ130mm*H66mm	Φ118mm	7W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-13009	4": Φ130mm*H66mm	Φ118mm	9W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-16009	5": Φ160mm*H70mm	Φ142mm	9W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-16012	5": Φ160mm*H70mm	Φ142mm	12W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-16015	5": Φ160mm*H70mm	Φ142mm	15W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-19012	6": Φ190mm*H70mm	Φ172mm	12W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-19015	6": Φ190mm*H70mm	Φ172mm	15W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-19018	6": Φ190mm*H70mm	Φ172mm	18W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-24015	8": Φ230mm*H85mm	Φ210mm	15W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-24018	8": Φ230mm*H85mm	Φ210mm	18W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DD-24021	8": Φ230mm*H85mm	Φ210mm	21W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DF-10003	2.5": Φ100mm*H70mm	Φ75mm	3W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DF-10005	2.5": Φ100mm*H70mm	Φ75mm	5W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DF-14005	4": Φ135mm*H66mm	Φ110mm	5W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DF-14007	4": Φ135mm*H66mm	Φ110mm	7W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DF-14009	4": Φ135mm*H66mm	Φ110mm	9W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DF-16509	5": Φ165mm*H71mm	Φ140mm	9W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w
SR-DF-16512	5": Φ165mm*H71mm	Φ140mm	12W	Aluminium+Acrylic	AC110-220V	50-60Hz	2700-6500K	>95lm/w



SUNRISE SYSTEM LIGHTING: DOWNLIGHTS

Model (A Series)	Dimension	Opening	Power	Housing Material	Input Voltage		Colour (Kelvin)	Lumen
SR0001000	∅ 52*H19mm	∅ 45mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0001001	∅ 68*H30mm	∅ 55mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0001002	∅ 82*H42mm	∅ 70mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0001003	∅ 78*H35mm	∅ 55mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0001006	∅ 68*H30mm	∅ 55mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0003001	∅ 86*H47mm	∅ 70-80mm	3W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0005001	∅ 105*H75mm	∅ 85-95mm	5W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0007001	∅ 105*H75mm	∅ 85-95mm	7W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0009001	∅ 138*H70mm	∅ 115-125mm	9W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0012001	∅ 138*H70mm	∅ 115-125mm	12W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0015001	∅ 160*H95mm	∅ 130-140mm	15W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0018001	∅ 160*H115mm	∅ 130-140mm	18W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0021001	∅ 180*H80mm	∅ 140-150mm	21	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0024001	∅ 180*H80mm	∅ 150-160mm	24	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0030001	∅ 230*H115mm	∅ 200-210mm	30	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w



SUNRISE SYSTEM LIGHTING: DOWNLIGHTS

Model (C Series)	Dimension	Opening	Power	Housing Material	Input Voltage		Colour (Kelvin)	Lumen
SR0001000	∅ 52*H19mm	∅ 45mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0001001	∅ 68*H30mm	∅ 55mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0001002	∅ 82*H42mm	∅ 70mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0001003	∅ 78*H35mm	∅ 55mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0001006	∅ 68*H30mm	∅ 55mm	1W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0003001	∅ 86*H47mm	∅ 70-80mm	3W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0005001	∅ 105*H75mm	∅ 85-95mm	5W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0007001	∅ 105*H75mm	∅ 85-95mm	7W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0009001	∅ 138*H70mm	∅ 115-125mm	9W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0012001	∅ 138*H70mm	∅ 115-125mm	12W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0015001	∅ 160*H95mm	∅ 130-140mm	15W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0018001	∅ 160*H115mm	∅ 130-140mm	18W	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0021001	∅ 180*H80mm	∅ 140-150mm	21	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0024001	∅ 180*H80mm	∅ 150-160mm	24	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w
SR0030001	∅ 230*H115mm	∅ 200-210mm	30	Aluminum	AC110-220V	50-60Hz	2700-3300K / 4000-4500K / 5700-6300K	>95lm/w

